



	Gusmer Enterprises, Inc.®		Issue Date: 12/04/15 Version: 1.0	
	<b>SAFETY DATA SHEET FORM</b>			
<b>Product Identifier:</b>		Gusmer Oak Products		
<b>Section 1 - PRODUCT and COMPANY IDENTIFICATION</b>				
<b>1.1 Product Identifier</b>				
Product Name:	Gusmer Oak Products: <b>Oak Mor:</b> Premium; Toasted, Toasted HT; Toasted LT; Toasted Fine Toast; Special; Toasted Euro Chip <b>Cellufine:</b> Cellufine 1; Cellufine 2; Cellufine H <b>Oak Advantage:</b> American Oak; French Oak <b>Granular Oak Infusion Bag;</b> Toasted Oak Mor Infusion, Premium Oak Mor Infusion, Avantage French Granular Oak Infusion, Avantage American Granular Oak Infusion			
Product Code(s):	<b>Oak Mor:</b> OMPREM; OMTOAST; OM-TOASTHT; OM-TOASTLT; OMECT-FINES; OMSPEC; OMECTOAST <b>Cellufine:</b> CELLUFINE1; CELLUFINE2; CELLUFINE-H <b>Oak Advantage:</b> AVANTAGE-AM; AVANCHIP-AM; AVANTAGE-FR; AVANCHIP-FR <b>Granular Oak Infusion Bag:</b> AVANINFUS-FR; AVANINFUS-AM; OMTOASTINF; OMPREMINF			
Chemical Name:	Oak Wood Granulated and Chips			
Synonyms:	Oak Mor; Avantage American & French Oak; Granular Oak Infusion Bag Quercus alba, white oak, Quercus rubra, Quercus sessiliflora, French oak			
<b>1.2 Relevant identified uses of the substance or mixture and uses advised against</b>				
Intended Product Use:	Flavor and color			
Uses Advised Against:	Avoid generating airborne dust.			
<b>1.3 Details of the supplier of the safety data sheet</b>				
Manufacturer/Distributor:	Gusmer Enterprises, Inc.			
Postal Address:	81 M Street, Fresno, CA 93721 USA	1401 Ware Street, Waupaca, WI 54981 USA		
Telephone Number:	(01)(659) 485-2692 [USA] (product info)	(01)(715) 258-5525 [USA] (product info)		
Hours of Operation:	Monday - Friday 8:00am-5:00pm PST	Monday - Friday 8:00am-5:00pm CST		
<b>1.4 Emergency telephone number</b>				
Medical Emergency:	911			
Chemical Emergency:	(800) 424-9300			
<b>Section 2 - HAZARDS IDENTIFICATION</b>				
<b>2.1 Classification of the substance or mixture:</b>				
<b>GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)</b>				
Carcinogenicity (Category 1A) Combustible Dust				
<b>2.2 Label Elements</b>				
<b>Hazard Pictogram(s):</b>		<b>Signal Word: Danger</b>		
				
<b>Hazard Statements:</b>		<b>Precautionary Statements:</b>		
May cause cancer by inhalation. May form combustible dust concentrations in air.		Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. IF exposed or concerned: Get medical advice/attention. Store locked up. Dispose of contents/ container to an approved waste disposal plant. Ventilation recommended.		
<b>2.3 Emergency Overview</b>				
Appearance/Odor:	<b>Oak Mor:</b> Toasted, Toasted HT; Toasted LT; Toasted Fine Toast; Special; Toasted Euro Chip - Brown to dark brown oak wood granules, powder and/or fragments. Typical oak odor. <b>Oak Mor: Premium</b> - Light tan to golden brown oak wood granules, powder and/or fragments. Typical oak odor. <b>Cellufine:</b> Cellufine 1; Cellufine 2; Cellufine H - Light tan to golden brown oak wood granules, powder and/or fragments. Typical oak odor. <b>Oak Advantage:</b> Toasted - Brown to dark brown oak wood granules, powder and/or fragments. Typical oak odor. <b>Oak Advantage: Untoasted</b> - Light tan to golden brown oak wood granules, powder and/or fragments. Typical oak odor. <b>Granular Oak Infusion Bag:</b> Toasted Oak Mor Infusion, Avantage French Granular Oak Infusion, Avantage American Granular Oak Infusion - Brown to dark brown oak wood granules, powder and/or fragments enclosed in a white Polypropylene Spunbound Nonwoven bag. Typical oak odor. <b>Granular Oak Infusion Bag: Premium Oak Mor Infusion</b> - Light tan to golden brown oak wood granules, powder and/or fragments enclosed in a white Polypropylene Spunbound Nonwoven bag. Typical oak odor.			
<b>Other Hazards:</b>	Warning: This product consists of white oak (Quercus alba) and French oak (Quercus rubra, Quercus sessiliflora) heartwood with no additives. The primary health hazard posed by this product is dust inhalation which can cause respiratory system irritation. Contact with skin and eyes can also cause irritation. Prolonged or repeated inhalation of wood dust may cause cancer. Wood dust is listed as a carcinogen by NTP, OSHA, and IARC. IARC - Group 1: Carcinogenic to humans; sufficient evidence of carcinogenicity.			
Product may form combustible dust concentrations in air during processing. Specifically, in instances where product dust is suspended in air in sufficient concentrations and in proximity to an ignition source. Users of this product should examine the potential to generate dusts during handling and processing and related combustibility hazards and controls.				
<b>Section 3 - COMPOSITION / INFORMATION on INGREDIENTS</b>				
<b>Ingredient(s)</b>	<b>Common Name &amp; Synonyms</b>	<b>Percentage</b>	<b>CAS No.</b>	
Granulated Oak Wood	Hard wood	>99%	NA	
Potassium Metabisulfite	Dipotassium disulphite	<0.4%	16731-55-8	
<i>Granular Oak Infusion Bag Products Only:</i>				
Infusion Bag:				
Polypropylene	Homopolymer	NA	9003-07-0	
Polypropylene, Isotactic	NA	NA	25085-53-4	
Aluminum Hydroxide	NA	NA	21645-51-2	
Titanium Dioxide	Rutile, Titanium Oxide	NA	13463-67-7	

	Gusmer Enterprises, Inc.®		Issue Date: 12/04/15 Version: 1.0	
	<b>SAFETY DATA SHEET FORM</b>			
<b>Product Identifier:</b>		Gusmer Oak Products		
<b>Section 4 - FIRST AID MEASURES</b>				
<b>4.1 Description of the first aid measures</b>				
Eye Contact:	Immediately flush eyes with copious amounts of water. If irritation develops, seek medical attention.			
Skin Contact:	Wash skin with plenty of soap and water. Get medical attention if irritation develops.			
Inhalation:	Move to fresh air. If not breathing, administer artificial respiration. If breathing is difficult, give oxygen. Seek medical attention.			
Ingestion:	If swallowed, Do Not Induce Vomiting. Give large quantities of water. Never give anything by mouth to an unconscious person. Seek medical attention.			
<b>4.2 Most important symptoms and effects, both acute and delayed</b>				
Eye Contact:	Contact may cause mild eye irritation with redness, tearing, and other vision effects.			
Skin Contact:	None under normal use. Sensitive individuals may develop contact dermatitis and may experience skin irritation. Symptoms may include itching.			
Inhalation:	None under normal use. Inhalation of high concentration of dusts may produce nasal dryness, irritation and obstruction. Coughing, wheezing, sneezing, sinusitis and prolonged colds may also develop. Excess inhalation of dust may cause asphyxiation.			
Ingestion:	Not a likely route of exposure under anticipated use conditions. If swallowed, may cause irritation of the gastrointestinal tract and discomfort with symptoms of nausea.			
Chronic Effects:	Chronic exposure to wood dusts can result in dermatitis reactions, asthma, pneumonitis, coughing, wheezing, fever and other signs and symptoms associated with chronic bronchitis. May also result in cancer (nose & throat).			
<b>4.3 Indication of any immediate medical attention and special treatment needed</b>				
Treatment:	No special advice, treat symptomatically.			
<b>Section 5 - FIREFIGHTING MEASURES</b>				
<b>5.1 Extinguishing Media</b>				
Suitable Extinguishing Media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.			
<b>5.2 Special hazards arising from the substance or mixture</b>				
Natural decomposition of organic materials such as wood may produce toxic gases and an oxygen deficient atmosphere in enclosed or poorly ventilated areas. Thermal decomposition (i.e. smoldering, burning) products include carbon monoxide, carbon dioxide, aliphatic aldehydes, terpenes, and polycyclic aromatic hydrocarbons.				
<b>Autoignition Temperature:</b> Variable [typically 400° - 500°F (204° - 260°F)]				
<b>5.3 Advice for firefighters</b>				
As in any fire, wear NIOSH-approved self contained breathing apparatus and appropriate protective clothing.				
<b>Explosion Hazards:</b> Depending on moisture content, and more importantly, particle diameter, wood dust may explode in the presence of an ignition source. For wood dust, an airborne concentration of 40 grams (40,000mg) of dust per cubic meter of air is often used as the LEL. Reference NFPA Standards 654 and 664 for guidance. Ventilation systems should be kept clean and precautions should be taken to prevent sparks or other ignition sources.				
<b>Section 6 - ACCIDENTAL RELEASE MEASURES</b>				
<b>6.1 Personal precautions, protective equipment and emergency procedures</b>				
Sweep or vacuum up for recovery and disposal. Avoid creating dusty conditions whenever feasible. Maintain good housekeeping to avoid accumulation of dust on exposed surfaces. Use NIOSH approved filtering face piece respirator ("dust mask") and goggles where ventilation is not possible and exposure limits may be exceeded or for additional worker comfort.				
Other precautions: Minimize compressed air blowdown or other practices that generate high dust levels.				
<b>6.2 Environmental precautions</b>				
None, discharge in accordance with federal, state and local laws.				
<b>6.3 Methods and materials for containment and cleaning up</b>				
If large amounts of dust are generated, collect with vacuum or suppress with water spray and sweep up.				
See Section 8 for appropriate personal protective equipment.				
<b>Section 7 - Handling and Storage</b>				
<b>7.1 Precautions for safe handling</b>				
Avoid generating excessive dust. If dust levels are suspected to be over PEL, wear a NIOSH approved N95 or greater respirator. Protect from excessive moisture. Maintain good housekeeping practices. See Section 8 for more information				
<b>7.2 Conditions for safe storage, including any incompatibilities</b>				
Store in cool, dry place away from open flame and other sources of ignition. Protect from excessive moisture and sun. Do not store next to vaporizable materials to avoid pick up of surrounding odors into the wood product.				
See Section 8 for OSHA permissible exposure limit(s)				
<b>Section 8 - EXPOSURE CONTROL / PERSONAL PROTECTION</b>				
<b>8.1 Control parameters</b>				
<b>Wood (wood dust)</b>	<b>OSHA PEL<sup>1</sup></b>	<b>ACGIH<sup>2</sup></b>	<b>NIOSH REL<sup>3</sup></b>	
	PEL-TWA 15 mg/m <sup>3</sup> Total Dust (PNOR) <sup>1</sup> PEL-TWA 5 mg/m <sup>3</sup> Respirable Dust (PNOR) <sup>1</sup>	TLV-TWA 1 mg/m <sup>3</sup> Inhalable Fraction	REL-TWA 1 mg/m <sup>3</sup>	
<b>Notes:</b>	1. OSHA particulate not otherwise regulated (PNOR)			
<b>8.2 Exposure controls</b>				
<b>Normal Handling Conditions</b>				
Engineering Controls:	If necessary use ventilation system to keep airborne dust concentration below permissible exposure limits. Ventilation to control dust should be considered where potential explosive concentrations and ignition sources are present. The design and operation of any exhaust system should consider the possibility of explosive concentrations of dust within the system.			
Ensure that exhaust ventilation and material transport systems involved in handling this product contain explosion relief vents or suppression systems designed and operated in accordance with applicable standards if the operating conditions justify their use.				
Respiratory Protection:	If dust levels are suspected to be over PEL, wear a NIOSH approved N95 or greater respirator.			
Eye Protection:	ANSI Z87+ approved dust goggles or safety glasses, if necessary, to avoid eye irritation.			
Skin Protection:	Cover skin with clothing and/or gloves if skin dryness or irritation occurs.			
General Hygiene:	Maintain good housekeeping practices, wash hands after handling, avoid direct eye contact. Clean up areas where dust settles to avoid excessive accumulation of this combustible material. Minimize compressed air blowdown or other practices that generate high airborne-dust concentrations.			

 <b>Gusmer Enterprises, Inc.®</b>	Issue Date: 12/04/15 Version: 1.0
<b>SAFETY DATA SHEET FORM</b>	
<b>Product Identifier:</b>	<b>Gusmer Oak Products</b>
<b>Section 9 - PHYSICAL and CHEMICAL PROPERTIES</b>	
<p><b>9.1 Information on basic physical and chemical properties</b></p> <p>Physical State: Solid          Color: See Section 2.3          Odor: Typical oak aroma          Odor Threshold: None          pH: No Data Available          Melting / Freezing Point (Specify): No Data Available          Initial Boiling Point &amp; Boiling Range: No Data Available          Flash Point: No Data Available          Evaporation Rate: No Data Available          Flammability (solid, gas): upper: No Data Available lower: No Data Available          Explosive Limits: 40,000 mg of dust per cubic meter of air is often used as the LEL for wood dusts.          Vapor Pressure: No Data Available          Vapor Density: No Data Available          Relative Density: No Data Available          Solubility(ies): &lt;0.1          Partition Coefficient (n-octanol/water): No Data Available          Auto-ignition Temperature: Variable [typically 400° - 500°F (204° - 260°F)]          Decomposition: No Data Available          Oxidizing Properties: No Data Available          Viscosity: No Data Available</p>	
<b>Section 10 - STABILITY and REACTIVITY</b>	
<p><b>10.1 Reactivity</b> No Data Available</p> <p><b>10.2 Chemical stability</b> Stable under recommended storage conditions.</p> <p><b>10.3 Possibility of hazardous reactions</b> None</p> <p><b>10.4 Conditions to avoid</b> Avoid open flame, sparks and other sources of ignition.</p> <p><b>10.5 Incompatible materials</b> Avoid contact with oxidizing agents and drying oils.</p> <p><b>10.6 Hazardous decomposition products</b> Natural decomposition of organic materials such as wood may produce toxic gases and an oxygen deficient atmosphere in enclosed or poorly ventilated areas. Thermal decomposition (i.e. smoldering, burning) products include carbon monoxide, carbon dioxide, aliphatic aldehydes, terpenes, and polycyclic aromatic hydrocarbons. Spontaneous and rapid hazardous decomposition will not occur.</p>	
<b>Section 11 - TOXICOLOGY INFORMATION</b>	
<p><b>11.1 Information on toxicological effects</b></p> <p><b>Toxicology Data:</b> The product has not been fully tested. The statements have been derived in parts from products of a similar structure or composition.</p> <p><b>Acute Toxicity:</b>  <i>Oral LD<sub>50</sub></i> No Data Available  <i>Dermal LD<sub>50</sub></i> No Data Available</p> <p><b>Skin Corrosion/Irritation:</b> Not expected to be a skin irritant under normal use. Some species of wood dust can cause allergic reactions (dermatitis) in sensitized individuals.</p> <p><b>Serious Eye Damage/Eye Irritation:</b> May cause eye irritation</p> <p><b>Respiratory or Skin Sensitization:</b> Not expected to be a sensitizing material under normal use. May cause transitory irritation to the nose, throat and lungs. Dusts generated from this material or product may cause nasal dryness, irritation, coughing or sinusitis. See Section 8 for exposure limits.</p> <p><b>STOT - Single Exposure:</b> Wood dust can cause eye irritation. Certain species of wood dust can elicit allergic contact dermatitis in sensitized individuals. Wood dust may cause respiratory irritation, nasal dryness, coughing, sneezing and wheezing as a result of inhalation.</p> <p><b>STOT - Repeated Exposure:</b> Wood dust, depending on the species, may cause allergic contact dermatitis and respiratory sensitization with prolonged, repetitive contact or exposure to elevated dust levels.</p> <p><b>Aspiration Hazard:</b> No Data Available</p> <p><b>11.2 Further Information</b></p> <p><b>Mutagenicity:</b> Exposure to wood dust may cause cellular changes in the nasal epithelium.</p> <p><b>Productive Toxicity:</b> No Data Available</p> <p><b>Carcinogenicity:</b> One or more of the ingredients are found on the following lists: Federal OSHA Z List, NTP, CAL/OSHA, IARC and therefore is considered to be, or suspected to be a cancer-causing agent by these agencies.</p> <p><b>Wood Dust - NTP:</b> According to its Report on Carcinogens, Twelfth Edition, NTP states, "Wood dust is known to be a human carcinogen based on sufficient evidence of carcinogenicity from studies in humans". An association between wood dust exposure and cancer of the nasal cavity has been observed in many case reports, cohort studies, and case-control studies that specifically addressed nasal cancer. Strong and consistent associations with cancer of the nasal cavities and paranasal sinuses were observed both in studies of people whose occupations are associated with wood dust exposure and in studies that directly estimated wood dust exposure. This classification is based primarily on increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust. The evaluation did not find sufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum with exposure to wood dust. There is inadequate evidence for the carcinogenicity of wood dust from studies in experimental animals according to NTP.</p> <p><b>Wood Dust - IARC - Group 1:</b> Carcinogenic to humans; sufficient evidence of carcinogenicity. This classification is primarily based on studies showing an association between occupational exposure to wood dust and adenocarcinoma to the nasal cavities and paranasal sinuses. IARC did not find sufficient evidence of an association between occupational exposure to wood dust and cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum.</p> <p><b>IARC:</b> Wood dust, Group 1 - carcinogenic to humans.  <b>NTP:</b> Wood dust - known human carcinogen.  <b>OSHA:</b> Not listed by OSHA</p>	

 <b>Gusmer Enterprises, Inc.</b> <sup>®</sup>	Issue Date: 12/04/15 Version: 1.0
	<b>SAFETY DATA SHEET FORM</b>
<b>Product Identifier:</b>	<b>Gusmer Oak Products</b>
<b>Section 12 - ECOLOGICAL INFORMATION</b>	
<p><b>12.1 Toxicity</b> No Data Available</p> <p><b>12.2 Persistence and degradability</b> No Data Available</p> <p><b>12.3 Bioaccumulative potential</b> Not expected to bioaccumulate.</p> <p><b>12.4 Mobility in soil</b> No Data Available</p> <p><b>12.5 Other adverse effects</b> No Data Available</p>	
<b>Section 13 - DISPOSAL CONSIDERATIONS</b>	
<p><b>Substance:</b> Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.</p>	
<b>Section 14 - TRANSPORTATION INFORMATION</b>	
<p><b>UN Number:</b> Not Applicable  <b>Class:</b> Not Applicable  <b>Proper Shipping Name:</b> Not Applicable  <b>Packing Group:</b> Not Applicable  <b>Marine Pollutant:</b> Not Applicable  <b>Other Applicable Information:</b> Not Applicable</p>	
<b>Section 15 - REGULATORY INFORMATION</b>	
<p><b>15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture</b></p> <p><b>OSHA:</b> Wood products per se are not hazardous under the criteria of the federal OSHA Hazard Communication Standard 29CFR 1910.1200. However, wood dust may be hazardous and hence included under 1910.1200.  <b>TSCA:</b> Not Applicable  <b>CERCLA:</b> Not Applicable  <b>SARA 302:</b> No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.  <b>SARA 313:</b> This material does not contain any chemical components with known CAS numbers that exceed the threshold reporting levels established by SARA Title III, Section 313.  <b>SARA 311/312:</b> This product has been reviewed according to the EPA's "Hazard Categories" promulgated under SARA Title III Sections 311 and 312 and is considered, under applicable definitions, to meet the following categories:              <b>An immediate (acute) health hazard:</b> Yes              <b>A delayed (chronic) health hazard:</b> Yes                  <b>A corrosive hazard:</b> No                  <b>A fire hazard:</b> No                  <b>A reactivity hazard:</b> No                  <b>A sudden release hazard:</b> No</p> <p><b>California Prop. 65 Components:</b>  <b>WARNING!</b> Wood dust is a substance known to the State of California to cause cancer.</p> <p><b>WHMIS Classification:</b> Class D-2-A - wood dust: IARC Group 1.</p>	
<b>Section 16 - OTHER INFORMATION</b>	
<p><b>Product Names/Number(s):</b></p> <p><b>Oak Mor:</b>          Premium Oak Mor - OMPREM          Toasted Oak Mor - OMTOAST          Toasted Oak Mor HT - OM-TOASTHT          Toasted Oak Mor LT - OM-TOASTLT          Toasted Oak Mor 2mm Chip-Fines - OMECT-FINES          Special Oak Mor - OMSPEC          Toasted Euro Chip - OMECTOAST</p> <p><b>Cellufine:</b>          Cellufine 1 Wood Cellulose - CELLUFINE1          Cellufine 2 Wood Cellulose - CELLUFINE2          Cellufine H Wood Cellulose - CELLUFINE-H</p> <p><b>Oak Advantage:</b>          Advantage American Oak Granular - AVANTAGE-AM          Advantage American Oak Chips - AVANCHIP-AM          Advantage French Oak Granular - AVANTAGE-FR          Advantage French Oak Chips - AVANCHIP-FR</p> <p><b>Granular Oak Infusion Bag:</b>          Toasted Oak Mor Infusion - OMTOASTINF          Premium Oak Mor Infusion - OMPREMINF          Advantage French Granular Oak Infusion - AVANINFUS-FR          Advantage American Granular Oak Infusion - AVANINFUS-AM</p> <p><b>Prepared By:</b> Gusmer Enterprises, Inc.      <b>Name of Preparer:</b> Eric Anderson  <b>Title:</b> Safety, Compliance &amp; GMP Manager  <b>Date:</b> 12/4/2015</p>	
<p><b>DISCLAIMER:</b> While the information in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by us for errors or omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances. Since the information contained in this document may be applied under conditions beyond our control, we can accept no responsibility for any loss or damage caused by any person acting or refraining from acting as a result of this information.</p>	



**SAFETY DATA SHEET FORM**

**Product Identifier:** Gusmer Oak Products

**GHS Hazard Warning Label**

**Gusmer Oak Products**



**DANGER:**  
May cause cancer by inhalation.  
May form combustible dust concentrations in air.

Obtain special instructions before use. Do not breathe dust. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. IF exposed or concerned: Get medical advice/attention. Store locked up, dispose of contents/ container to an approved waste disposal plant. Ventilation recommended.

Gusmer Enterprises Inc.  
81 M St. Fresno, CA 93721 (559) 485-2692  
1401 Ware Street, Waupaca, WI 54981 (715) 258-5525

**CONSULT SDS FOR ADDITIONAL INFORMATION ON HAZARD**

V1.0